

Excavators / E20 Compact Excavator

Specifications & Options

■ Standard
 Optional
N/A Not Applicable

Bobcat E20

⊖ Engine

	Standard arm	Long arm
Emissions Tier (EPA)	Tier 4	Tier 4
Engine Fuel	Diesel	Diesel
Maximum Governed RPM	2,500 rpm	2,500 rpm
Horsepower	10.4 kW	10.4 kW
Turbocharged Engine	N/A	N/A

⊖ Performance

	Standard arm	Long arm
Operating Weight	1930 kg	1953 kg
Weight Class	2 t	2 t
Travel Speed - High	4 km/h	4 km/h
Travel Speed - Low	2.5 km/h	2.5 km/h
Arm Digging Force	10,371 N	9,279 N
Bucket Digging Force	20,835 N	20,835 N
Boom Swing - Left	80°	80°
Boom Swing - Right	60°	60°
Maximum Dig Depth	2.4 m	2.6 m
Max Dump Height	2.6 m	2.7 m
Maximum Reach at Ground Level	4.1 m	4.3 m

⊖ Capacities

	Standard arm	Long arm
Fuel Tank	19 L	19 L

⊖ Hydraulic System

	Standard arm	Long arm
Auxiliary Std Flow	30 l/min	30 l/min
Auxiliary Pressure	180 bar	180 bar

⊖ Dimansion

	Standard arm	Long arm
Length	3688 mm	3669 mm
Overall Length in Travel Position	3688 mm	3669 mm
Width	980 mm	980 mm
Height	2297 mm	2297 mm

⊖ Features

Cab Enclosure	<input checked="" type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Cab Air Conditioning	N/A
Radio	<input checked="" type="checkbox"/>
Tail Swing Type	Zero
Engine Shutdown	<input type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Secondary Auxiliary Hydraulics	N/A
Quick Tach System	N/A
Rubber Track	<input type="checkbox"/>
Selectable Auxiliary Hydraulic Flow	<input type="checkbox"/>
Angle Blade	N/A

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.